



TurboFog Neo Technical Data

Information on the TurboFog Neo phase-in

Beginning 01/06/2012, the TurboFog family will be replaced by a new product series. Until now, the TurboFog atomizer has been available as a standard version and in stainless steel.

The next generation will be available only in stainless steel.

The following is a list of the devices including technical data.

TurboFogNeo 1 US

(Old name TurboFog 4 US)

Max. hum. output	8 lbs/hr
Operating voltage	120VAC, 60Hz ; 24VDC
Input power	6.2 W
Weight	2.2 lbs
Service no. new device	009727



TurboFogNeo 2 US

(Old name TurboFog 8 US)

Max. hum. output	17 lbs/hr
Operating voltage	120VAC, 60Hz ; 24VDC
Input power	6.2 W
Weight	2.3 lbs
Service no. new device	009728



DRAABE

TurboFogNeo 2x1 US
(Old name TurboFog 8.2 US)

Max. hum. output	17 lbs/hr
Operating voltage	120VAC, 60Hz; 24VDC
Input power	12.4 W
Weight	4.8 lbs
Service no. new device	009738



TurboFogNeo 2x2 US
(Old name TurboFog 16 US)

Max. hum. output	35 lbs/hr
Operating voltage	120VAC, 60Hz ; 24VDC
Input power	12.4 W
Weight	5.4 lbs
Service no. new device	009739



TurboFogNeo 8 US
(Old name TurboFog 32 US)

Max. hum. output	70 lbs/hr
Operating voltage	120VAC, 60Hz
Input power	34 W
Weight	17.6 lbs
Service no. new device	009729

